



BREEZE POT POURRI

K122

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code K122

Manufacturer : Selden Research Limited
Staden Lane Business Park, Staden Lane,
Buxton, Derbyshire. SK17 9RZ
United Kingdom

Product Name BREEZE POT POURRI

Tel : 01298 26226
Fax : 01298 26540
Email : sales@selden.co.uk

2 HAZARDS IDENTIFICATION

R12 Extremely flammable.
PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

Classification F+;R12.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
PROPAN-2-OL	200-661-7	67-63-0	1 - 5%	F;R11 Xi;R36 R67

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION Move the exposed person to fresh air at once., Keep the affected person warm and at rest. Get prompt medical attention., For breathing difficulties oxygen may be necessary.

INGESTION Rinse mouth thoroughly., Drink plenty of water., Get medical attention.

SKIN CONTACT Wash the skin immediately with soap and water., Get medical attention if any discomfort continues.

EYE CONTACT Promptly wash eyes with plenty of water while lifting the eye lids., Continue to rinse for at least 15 minutes., Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA Use:, Powder., Dry chemicals, sand, dolomite etc., Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES Containers close to fire should be removed or cooled with water., Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Wear necessary protective equipment., Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate., If leakage cannot be stopped, evacuate area.

ENVIRONMENTAL PRECAUTIONS Any spillage needs to be contained and not allowed to enter water courses

7 HANDLING AND STORAGE

USAGE PRECAUTIONS Keep away from heat, sparks and open flame., Avoid spilling, skin and eye contact., Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

USAGE DESCRIPTION Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES Provide adequate general and local exhaust ventilation.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Aerosol

PHYSICAL DATA COMMENTS Information given relates to total aerosol container contents.

FLASH POINT (°C) - 74 N/A.

AUTO IGNITION TEMPERATURE (°C) + 405

FLAMMABILITY LIMIT - LOWER(%) 1.8

FLAMMABILITY LIMIT - UPPER(%) 10.0

10 STABILITY AND REACTIVITY

STABILITY Stable under normal temperature conditions.

CONDITIONS TO AVOID Avoid heat, flames and other sources of ignition., Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.

HAZARDOUS DECOMPOSITION PRODUCTS Fire creates:, Toxic gases/vapours/fumes of:, Carbon monoxide (CO), Carbon dioxide (CO2).

11 TOXICOLOGICAL INFORMATION

INHALATION	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting., Gas or vapour displaces oxygen available for breathing (asphyxiant)., Unconsciousness.
SKIN CONTACT	No specific health warnings noted.
EYE CONTACT	Irritation of eyes and mucous membranes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY	Not regarded as dangerous for the environment.
-------------	--

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS	Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.
------------------	--

14 TRANSPORT INFORMATION

UN NO. ROAD	1950
UK ROAD CLASS	2
ADR CLASS NO.	2 Class Code:5F Label: 2.1
PROPER SHIPPING NAME	AEROSOLS, FLAMMABLE
UN NO. SEA	1950
IMDG CLASS	2.1
IMDG PACK GR.	N/A
UN NO. AIR	1950
AIR CLASS	2.1
AIR PACK GR.	N/A

15 REGULATORY INFORMATION

LABELLING



Extremely Flammable (F+)

RISK PHRASES	R12 Extremely flammable.
SAFETY PHRASES	A1 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use., A2 Do not spray on a naked flame or any incandescent material., S16 Keep away from sources of ignition - No smoking., S51 Use only in well-ventilated areas., S2 Keep out of the reach of children
STATUTORY INSTRUMENTS	Control of Substances Hazardous to Health., Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE	Classification and Labelling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES	Workplace Exposure Limits EH40., Introduction to Local Exhaust Ventilation HS(G)37., CHIP for everyone HSG(108).

16 OTHER INFORMATION

GENERAL INFORMATION	The following risk phrases relate to the raw materials in the product and not the product itself:-
REVISION DATE	21/12/2011
REV. NO./REPL. SDS GENERATED	7
RISK PHRASES IN FULL	R11 Highly flammable., R36 Irritating to eyes., R67 Vapours may cause drowsiness and dizziness.]